



### System Includes:

Cat No: 11000-100

- Optical Mapper
- MapCard Processor
- Mapping Work Station
- Oil Applicator
- MapSolver™ Software
- One year instrument warranty
- Set-up and Installation
- Training

### Additional

Argus™ MapCard Processor

Cat No: 11100-001

### Specifications

#### Argus™ MapCard Processor

Dimensions (W x D x H in)	10.75 x 18.5 x 10.5
Weight (lbs)	32
Power	1 Primary Power Receptacle, 3.2 A/1.6A, 100–127/220 240 VAC 50–60 Hz
Network Requirements	1 RJ45 1Gb Ethernet port
Operating Temperature	20–27°C (68–81°F)
Operating Humidity	Non-condensing; 15–65% RH

#### Argus™ Optical Mapper

Dimensions (W x D x H in)	38 x 21.5 x 19.75
Weight (lbs)	95
Power	2 Primary Power Receptacles, 8A/4A, 100–127/220–240 VAC 50–60 Hz
Network Requirements	1 RJ45 1Gb Ethernet port
Operating Temperature	20–24°C (71–75°F)
Operating Humidity	Non-condensing; 15–65% RH

#### Argus™ Oil Applicator

Dimensions (W x D x H in)	6.25 x 6.25 x 13
Weight (lbs)	10
Power	1 Primary Power Receptacle, .2A/.1A, 100–127/220–240 VAC 50–60 Hz
Network Requirements	N/A
Operating Temperature	20–24°C (71–75°F)
Operating Humidity	Non-condensing; 15–65% RH

#### Argus™ Mapping Workstation

Dimensions (W x D x H in)	18.75 x 9 x 15
Weight (lbs)	18
Power	1 Primary Power Receptacle, 2A/1A, 100–127/220–240 VAC 50–60 Hz
Network Requirements	1 RJ45 1Gb Ethernet port
Operating Temperature	20–27°C (68–81°F)
Operating Humidity	Non-condensing; 15–65% RH



### Argus™ Product Support

To place an Argus System order, please contact Customer Support at one of the following:

<b>Customer Support</b>	<b>CustomerSupport@OpGen.com</b>
<b>US toll free</b>	<b>888.856.2748</b>
<b>Corporate fax</b>	<b>301.869.9684</b>
<b>International</b>	<b>301.869.9683</b>

To locate OpGen Distribution Partners, or learn more about Optical Mapping Technology, please visit our website at [www.OpGen.com](http://www.OpGen.com).